

Model	AQLH-26	AQLH-32	AQLH-42	AQLH-55	AQLH-65	AQLH-70	AQLH-82
LCD Pannel	26inch	32inch	42inch	55inch	65inch	70inch	82inch
Resolution	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p
Brightness	1,500 Nits	1,500 Nits	1,500 Nits	1,500 Nits	1,500 Nits	1,500 Nits	1,500 Nits
Contrast	10,000:1	10,000:1	10,000:1	10,000:1	10,000:1	10,000:1	10,000:1
Response time	6 ms	6 ms	6 ms	6 ms	6 ms	6 ms	6 ms
Viewing angle	170°	170°	170°	170°	170°	170°	170°
Glass	Tempered AR glass	Tempered AR glass	Tempered AR glass	Tempered AR glass	Tempered AR glass	Tempered AR glass	Tempered AR glass
IP Certificated	IP66	IP66	IP66	IP66	IP66	IP66	IP66
Power supply	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug
Video standard	PAL/SECAM	PAL/SECAM	PAL/SECAM	PAL/SECAM	PAL/SECAM	PAL/SECAM	PAL/SECAM
Working temp	(- 20°C to + 55°C)	(- 20°C to + 55°C)	(- 20°C to + 55°C)	(- 20°C to + 55°C)	(- 20°C to + 55°C)	(- 20°C to + 55°C)	(- 20°C to + 55°C)
Working humidity	10% - 90%	10% - 90%	10% - 90%	10% - 90%	10% - 90%	10% - 90%	10% - 90%
Speaker pair	Yes (External)	Yes (External)	Yes (External)	Yes (External)	Yes (External)	Yes (External)	Yes (External)
Media support	USB interface	USB interface	USB interface	USB interface	USB interface	USB interface	USB interface
Play format	MPEG 1-4 & more	MPEG 1-4 & more	MPEG 1-4 & more	MPEG 1-4 & more	MPEG 1-4 & more	MPEG 1-4 & more	MPEG 1-4 & more
Tuner format	ATV & DTV	ATV & DTV	ATV & DTV	ATV & DTV	ATV & DTV	ATV & DTV	ATV & DTV
Control	IR & RS232**	IR & RS232**	IR & RS232**	IR & RS232**	IR & RS232**	IR & RS232**	IR & RS232**
Power Consumption	>120 Watts	>120 Watts	>230 Watts	>475 Watts	>750 Watts	>1,000 Watts	TBC
Standby Mode	0.6 Watts	0.6 Watts	0.7 Watts	1.5 Watts	2.0 Watts	2.5 Watts	TBC
Boxed weight	28 Kgs	44 Kgs	51 Kgs	88 Kgs	127 Kgs	150 Kgs	300 Kgs
Net weight	22 Kgs	34 Kgs	42 Kgs	70 Kgs	105 Kgs	135 Kgs	201 Kgs
Outer carton dimensions (mm)	TBC	L990xH710xD233	L1225xH855xD233	L1560xH1015xD233	L1780xH1150xD233	TBC	L2500xH1500x350
Screen dimensions (mm)	L756xH511.5xD137.5	L866xH581xD138	L1087xH685xD138	L1419xH844xD138	L1641xH976xD138	L1770xH1051x138	L2011xH1182xD145
Inputs	HDMI, VGA, Componet, RF (aerial), S-Video, Composite (RCA), Audio left/right (RCA), RS2323, USB						
Outputs	Audio left/right(RCA), Speaker cbles (pair-from internal 12W per channel amp)						
	RS232** Please note that all up to date RS232 functionality should be checked with manufacturer before purchase						

Model	AQLS-26	AQLS-32	AQLS-42	AQLS-55	AQLS-65	AQLS-70	AQLS-82
LCD Pannel	26inch	32inch	42inch	55inch	65inch	70inch	82inch
Resolution	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p
Brightness	500 Nits	500 Nits	500 Nits	500 Nits	500 Nits	500 Nits	500 Nits
Contrast	10,000:1	10,000:1	10,000:1	10,000:1	10,000:1	10,000:1	10,000:1
Response time	6 ms	6 ms	6 ms	6 ms	6 ms	6 ms	6 ms
Viewing angle	170°	170°	170°	170°	170°	170°	170°
Glass	Tempered AR glass	Tempered AR glass	Tempered AR glass	Tempered AR glass	Tempered AR glass	Tempered AR glass	Tempered AR glass
IP Certificated	IP66	IP66	IP66	IP66	IP66	IP66	IP66
Power supply	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug
Video standard	PAL/SECAM	PAL/SECAM	PAL/SECAM	PAL/SECAM	PAL/SECAM	PAL/SECAM	PAL/SECAM
Working temp	(- 20°C to + 55°C)	(- 20°C to + 55°C)	(- 20°C to + 55°C)	(- 20°C to + 55°C)	(- 20°C to + 55°C)	(- 20°C to + 55°C)	(- 20°C to + 55°C)
Working humidity	10% - 90%	10% - 90%	10% - 90%	10% - 90%	10% - 90%	10% - 90%	10% - 90%
Speaker pair	Yes (External)	Yes (External)	Yes (External)	Yes (External)	Yes (External)	Yes (External)	Yes (External)
Media support	USB interface	USB	USB	USB	USB	USB	USB
Play format	MPEG 1-4 & more	MPEG 1-4 & more	MPEG 1-4 & more	MPEG 1-4 & more	MPEG 1-4 & more	MPEG 1-4 & more	Mpeg 1-4 & more
Tuner format	ATV & DTV	ATV & DTV	ATV & DTV	ATV & DTV	ATV & DTV	ATV & DTV	ATV & DTV
Control	IR & RS232**	IR & RS232**	IR & RS232**	IR & RS232**	IR & RS232**	IR & RS232**	IR & RS232**
Power Consumption	>120 Watts	>115 Watts	>200 Watts	>260 Watts	>490 Watts	>800 Watts	TBC
Standby Mode	0.6 Watts	1.5 Watts	0.5 Watts	0.3 Watts	0.5 Watts	0.7 Watts	TBC
Boxed weight	28 Kgs	39 Kgs	48 Kgs	85 Kgs	105 Kgs	145 Kgs	300 Kgs
Net weight	22 Kgs	29 Kgs	38 Kgs	75 Kgs	95 Kgs	125 Kgs	201 Kgs
Outer carton dimensions (mm)	TBC	L990xH710xD233	L1225xH855xD233	L1560xH1015xD233	L1780xH1150xD233	TBC	L2500xH1500x350
Screen dimensions (mm)	L756xH511.5xD137.5	L866xH581xD97.5	L1087xH685xD138	L1419xH844xD138	L1641xH976xD138	L1770xH1051x138	L2011xH1182xD145
Inputs	HDMI, VGA, Componet, RF (aerial), S-video, Composite (RCA), Audio left/right (RCA), RS232, USB						
Outputs	Audio left/right (RCA), Speaker cables (pair - from internal 12W per channel amp)						